

## **PP-2150-MFill3**

### **Polypropylene Compound Reinforced with Glass Fiber**

### **Injection Grade**



### Technical Data Sheet

---

#### **Product Description**

**PP-2150-MFill3** is Homo-polymer Polypropylene based Compound in natural color reinforced with 30% of Chopped Glass Fiber. This grade has good mechanical properties, impact resistance, thermal properties and dimensional stability. It is designed for use in a wide range of injection parts especially in automotive industry.

---

---

#### **General**

Material Status: Available  
Processing Method: injection molding  
Form: Pellet  
Color: Natural

---

---

#### **Properties**

<b>Properties</b>	<b>Nominal Value</b>	<b>Test Method</b>
Density	1.12 g/cm <sup>3</sup> (±0.01)	ASTM D792
MFI (230°C/ 2.16kg)	5 g/10 min (±1)	ASTM D1238
Izod Impact, Notched	9 kJ/m <sup>2</sup> (±1)	ISO 180
Tensile Strength at Yield	75 MPa (±5)	ASTM D638
Elongation at Break	4% (±1)	ASTM D638
Elastic Modulus	4000 MPa (±200)	ASTM D638
Heat Deflection Temperature (0.45MPa)	165 °C (±5)	ASTM D648

---

Typical Properties: These values are not to be considered as product specifications

For more details please contact us

[www.modiranpolymer.com](http://www.modiranpolymer.com)